



Endcap				
Nominal Pipe Size	Outside Diameter	Wall thickness	Height	Weight
DN	D	Wt	H	Kg
10	17.2	2.0	11.5	0.01
-	20.0	2.0	12.0	0.01
15	21.3	2.0	14.5 / 25.0	0.02 / 0.05
15	21.3	2.6	25.0	0.08
15	21.3	3.0	15.5	0.02
-	25.0	2.0	12.0	0.02
20	26.9	2.0	10.5 / 25.0	0.02 / 0.06
20	26.9	2.6	25.0	0.08
20	26.9	3.0	12.0	0.02
-	28.0	2.0	12.0	0.02
-	30.0	2.0	12.0	0.02
25	33.7	2.0	12.5 / 38.0	0.02 / 0.06
25	33.7	2.6	38.0	0.08
25	33.7	3.0	14.5	0.04
25	33.7	3.2	38.0	0.09
-	38.0	2.0	15.0	0.03
-	40.0	2.0	14.0	0.03
32	42.4	2.0	17.0 / 38.0	0.04 / 0.08
32	42.4	2.6	38.0	0.10
32	42.4	3.0	18.0	0.06
32	42.4	3.2	38.0	0.12
-	44.5	2.0	16.0	0.04
40	48.3	2.0	17.0 / 38.0	0.05 / 0.10
40	48.3	2.6	38.0	0.13
40	48.3	3.0	23.0	0.12
40	48.3	3.2	38.0	0.15
-	50.8	2.0	19.0	0.06
-	54.0	2.0	19.0	0.06
-	56.0	3.0	19.0	0.12
-	57.0	2.0	22.0	0.08
-	57.0	3.0	22.0	0.11
50	60.3	2.0	20.0 / 38.0	0.08 / 0.15
50	60.3	2.6	38.0	0.19
50	60.3	3.0	22.0 / 38.0	0.12 / 0.22
50	60.3	3.6	38.0	0.26
50	60.3	4.0	22.0	0.15
-	63.5	2.0	19.0	0.08
-	70.0	2.0	21.0	0.10
-	71.0	3.0	21.0	0.10
65	76.1	2.0	27.0	0.13
65	76.1	3.0	29.0 / 38.0	0.20 / 0.24
65	76.1	4.0	29.0	0.26
-	84.0	2.0	23.0	0.13
-	86.0	3.0	23.0	0.20
80	88.9	2.0	29.0	0.17
80	88.9	3.0	30.0 / 51.0	0.25 / 0.37
80	88.9	4.0	30.0	0.33
-	104.0	2.0	24.0	0.19

Endcap				
Nominal Pipe Size	Outside Diameter	Wall thickness	Height	Weight
DN	D	Wt	H	Kg
-	106.0	3.0	25.0	0.28
-	108.0	2.0	32.0	0.25
-	108.0	3.0	34.0	0.37
-	108.0	4.0	34.0	0.49
100	114.3	2.0	32.0	0.25
100	114.3	3.0	32.0 / 64.0	0.37 / 0.57
100	114.3	4.0	32.0	0.49
-	129.0	2.0	34.0	0.31
-	131.0	3.0	35.0	0.47
-	133.0	2.0	34.0	0.31
-	133.0	3.0	34.0	0.47
-	133.0	4.0	34.0	0.71
125	139.7	2.0	35.0	0.37
125	139.7	3.0	36.0 / 76.0	0.57 / 1.00
125	139.7	4.0	36.0	0.71
-	154.0	2.0	41.0	0.44
-	156.0	3.0	42.0	0.82
-	159.0	2.0	42.0	0.44
-	159.0	3.0	42.0	0.67
-	159.0	4.0	42.0	1.15
150	168.3	2.0	40.0	0.52
150	168.3	3.0	43.0 / 89.0	0.78 / 1.13
150	168.3	4.0	43.0	1.15
-	204.0	2.0	50.0	0.75
-	206.0	3.0	50.0	1.13
200	219.1	2.0	50.0	0.85
200	219.1	3.0	51.0 / 102.0	1.27 / 1.97
200	219.1	4.0	51.0	1.87
-	254.0	2.0	55.0	1.08
-	256.0	3.0	55.0	1.62
250	273.0	2.0	63.0	1.31
250	273.0	3.0	62.0 / 127.0	1.97 / 4.03
250	273.0	4.0	62.0	3.62
-	304.0	2.0	68.0	1.65
-	306.0	3.0	70.0	2.47
300	323.9	2.0	72.0	1.81
300	323.9	3.0	72.0 / 152.0	2.72 / 5.74
300	323.9	4.0	72.0	3.63
350	355.6	3.0	89.0 / 165.0	3.52 / 6.53
350	355.6	4.0	89.0	5.32
400	406.4	3.0	98.0 / 178.0	4.52 / 8.21
400	406.4	4.0	98.0	6.53
450	457.2	3.0	107.0 / 203.0	5.49 / 10.42
450	457.2	4.0	107.0	5.49
500	508.0	3.0	120.0 / 229.0	6.56 / 12.52
500	508.0	4.0	120.0	10.29
600	609.6	3.0	140.0 / 267.0	9.23 / 17.60
600	609.6	4.0	140.0	14.13